



EHS800/1900X65-17/19E

Dual band antenna variable electrical tilt

Main Specification

Polarisation	Xpol +45° -45°
Gain	17 / 19 dBi
HBW	65°
Elec Downtilt	0-8°

Electrical Specifications			Units			
Frequency	MHz	820-896	870-960	1710-1990	1920-2170	
Gain	dBi	16.5	17	19	19.5	
VSWR		1.5	1.5	1.5	1.5	
Isolation	dB	>30	>30	>30	>30	
Horizontal Beam width	degree	67	65	66	63	
Vertical Beam Width	degree	8	7.5	4.5	4	
Electrical Downtilt	degree	0-8	0-8	0-6	0-6	
Front To Back Ratio	dB	>25	>25	>25	>25	
Impedance	Ohms	50	50	50	50	
Intermodulation 3rd Order	dBm	-150	-150	-150	-150	
Maximum Power Input	W	200	200	200	200	
Lightning Protection			DC Ground			

Mechanical Specifications

Input Connector	4 x 7/16 DIN Female
Connector Location	Bottom
Dimension H x W x D	2580 x 268 x 138mm
Weight	26 kg
Radome Material / Colour	UV PVC
Mechanical Tilt	0-10



CostWORX is the leading wholesale distributor of telecom & technology infrastructure products, supplying globally through a network of local alliance partners.

Operating Temperature

-40~60