



36000BTU Split Unit With Compressor

Standard split unit air conditioning system.

Providing cooling and dehumidification for telecommunications equipment enclosures.

CE/ROHS Compliant.

Capacity

BTU/H	36000
-------	-------

Min / Max	
-----------	--

Electrical Data

Voltage & Frequency	220-240V & 50Hz
---------------------	-----------------

Power Input	3570W
-------------	-------

Operating Current	17A
-------------------	-----

Performance

Dehumidifying Volume	3.8L/H
----------------------	--------

Air Flow Volume (Indoor)	1350m³/h
--------------------------	----------

Noise Level Outdoor	65dB(A)
---------------------	---------

Net Dimensions & Weight

Indoor Unit WxDxH	1200x242x383mm
-------------------	----------------

Outdoor Unit WxDxH	1030x505x855mm
--------------------	----------------

Gross Weight Indoor / Outdoor	20/84kg
-------------------------------	---------

Key Features

- Low Voltage Start - Able to work normally at between 187 - 240 Volts
- Rust Free - 6 coating protection system applied to the outdoor unit



CostWORX is the leading wholesale distributor of telecom & technology infrastructure products, supplying globally through a network of local alliance partners.

- Self Protection System - Detects errors and prevents damage to unit
- Super Quiet - Both indoor and outdoor units are designed to minimise noise

Certification

CE Approved

UL Approved