



60m 3-Leg Tower - 5m² Loading

Optimised for cellular telecom applications, this structure is produced with deployment and operation in mind and is capable of supporting 5m² of antenna load whilst remaining within a deflection limit of 0.5° at operational wind speed.

Produced from premium steel members hot dip galvanised equivalent to ASTM A123 (2000) and connected with high grade galvanised bolts, this structure has a design life in excess of 25 years.

Export packed and supplied with holding down bolts, anchor plates and setting template, this product is the quality choice.

| Loading | Height | Type | Area |
|-------------|--------------|-----------------------|------------------------|
| Distributed | Over Top 10m | Antenna Loading | 5m ² |
| Linear | Vertical Run | Feeder Cable & Ladder | 0.40 m ² /m |

| Design Wind Speeds (3 Second Gust) | |
|------------------------------------|----------|
| Basic Wind Speed | 39.0 m/s |
| Operational Wind Speed | 33.0 m/s |

| Deflection | |
|-----------------------|----------------------------------|
| Less than or Equal to | 0.5° (at Operational Wind Speed) |

| Design Parameter | |
|----------------------|---|
| Structure Class | 2 |
| Exposure Category | C |
| Topographic Category | 1 |

Design Standards

| Material | Standard | Steel Grade | Tensile Strength | Yield Strength |
|------------------|------------|-------------|-----------------------|-----------------------|
| Structural Steel | JIS G 3444 | STK 41 | 402 N/mm ² | 235 N/mm ² |
| | JIS G 3101 | SS 400 | 310 N/mm ² | 245 N/mm ² |
| Structural Bolts | BS 3692 | 8.8 | 830 N/mm ² | 664 N/mm ² |



CostWORX is the leading wholesale distributor of telecom & technology infrastructure products, supplying globally through a network of local alliance partners.

Codes of Practice

ANSI/TIA 222-G : 2005 - Structural Standard for Steel Antenna Tower and Antenna Support Structures

ANSI/AISC 360-05 : 2005 - America Institute of Steel Construction

Galvanization Equivalent to ASTM A123 (2000)

Features

| | |
|-------------------------|-------------------------------|
| - Internal Caged Ladder | |
| - Work Platform | 5m Below Top |
| - Rest Platform | 10.0m / 20.8m / 32.4m / 44.0m |
| - Holding Down Bolt Kit | |
| - Setting Template | |
| - Lightning Spike | |